



Cambridge Part#	Length (L)	Width (W)	Thickness (T)	Max Bundle Dia.
CT8-120	7.87 [200]	0.30 [7.6]	0.072 [1.83]	1.97 [50]
CT11-120	11.02 [280]	0.30 [7.6]	0.072 [1.83]	2.80 [71]
CT14-120	14.49 [368]	0.30 [7.6]	0.072 [1.83]	4.02 [102]
CT17-120	16.93 [430]	0.30 [7.6]	0.072 [1.83]	4.92 [125]
CT21-120	20.87 [530]	0.30 [7.6]	0.072 [1.83]	5.51 [140]

*Please Inquire About Other Sizes Not Listed
 **See Cambridge Catalog for Colors and Packaging Options



PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF **CODA RESOURCES**. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF **CODA RESOURCES** IS PROHIBITED.

Rated Operating Temperatures:
 -40°F to 185°F (-40°C to 85°C)

Usage Recommendations:

The cable ties must be stored at room temperature in at least 50% humidity (recommended 80%RH) in a completely sealed polyethylene bag if not being used. In extreme heat and cold, limit the exposure of unused cable ties. If after being exposed to extreme temperatures and/or extreme relative humidities, the cable ties must be allowed to be stored at room temperature and at least 50% humidity (recommended 80%RH) for at least 24 hrs in a sealed bag before being used again

	NAME	DATE	CAMBRIDGE 960 Alabama Ave, Brooklyn, NY 11207 P:718-649-1666 F:718-485-4403		
DRAWN	J Li	10/17/06			
UNLESS OTHERWISE SPECIFIED:			TITLE:		
DIMENSIONS ARE IN INCHES [] DENOTES MILLIMETER			Cambridge Cable Ties 120lb Tensile Strength		
MATERIAL Nylon 6,6 94V-2			SIZE	DWG. NO.	REV
FINISH			A	CT-120 REV A	A
DO NOT SCALE DRAWING			SCALE: 1:1	WEIGHT:	SHEET 1 OF 1