



Cambridge Part#	Length (L)	Width (W)	Thickness (T)	Max Bundle Dia.
CT4-18	3.94 [100]	0.10 [2.5]	0.04 [1.01]	0.87 [22]
CT5-18	5.51 [140]	0.10 [2.5]	0.04 [1.01]	1.30 [33]
CT8-18	7.87 [200]	0.10 [2.5]	0.04 [1.01]	2.09 [53]

*Please Inquire About Other Sizes Not Listed
 **See Cambridge Catalog for Colors and Packaging Options



PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF **CODA RESOURCES**. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF **CODA RESOURCES** IS PROHIBITED.

Rated Operating Temperatures:
 -40°F to 185°F (-40°C to 85°C)

Usage Recommendations:
 The cable ties must be stored at room temperature in at least 50% humidity (recommended 80%RH) in a completely sealed polyethylene bag if not being used. In extreme heat and cold, limit the exposure of unused cable ties. If after being exposed to extreme temperatures and/or extreme relative humidities, the cable ties must be allowed to be stored at room temperature and at least 50% humidity (recommended 80%RH) for at least 24 hrs in a sealed bag before being used again

	NAME	DATE	CAMBRIDGE 960 Alabama Ave, Brooklyn, NY 11207 P:718-649-1666 F:718-485-4403		
DRAWN	J Li	10/17/06			
UNLESS OTHERWISE SPECIFIED:			TITLE: Cambridge Cable Ties 18lb Tensile Strength		
DIMENSIONS ARE IN INCHES [] DENOTES MILLIMETER			SIZE	DWG. NO.	REV
MATERIAL Nylon 6,6 94V-2			A	CT-18 REV A	A
FINISH			DO NOT SCALE DRAWING	SCALE: 1:1	WEIGHT: SHEET 1 OF 1