



Cambridge Part#	Length (L)	Width (W)	Thickness (T)	Max Bundle Dia.
CT9-250	9.06 [230]	0.50 [12.7]	0.087 [2.20]	1.97 [50]
CT18-250	18.90 [480]	0.50 [12.7]	0.087 [2.20]	4.72 [120]
CT23-250	22.83 [580]	0.50 [12.7]	0.087 [2.20]	5.98 [152]
CT29-250	28.74 [730]	0.50 [12.7]	0.087 [2.20]	8.03 [204]
CT35-250	34.64 [880]	0.50 [12.7]	0.087 [2.20]	9.76 [248]
CT40-250	40.55 [1030]	0.50 [12.7]	0.087 [2.20]	11.61 [295]

*Please Inquire About Other Sizes Not Listed
 **See Cambridge Catalog for Colors and Packaging Options



PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF **CODA RESOURCES**. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF **CODA RESOURCES** IS PROHIBITED.

Rated Operating Temperatures:
 -40°F to 185°F (-40°C to 85°C)

Usage Recommendations:
 The cable ties must be stored at room temperature in at least 50% humidity (recommended 80%RH) in a completely sealed polyethylene bag if not being used. In extreme heat and cold, limit the exposure of unused cable ties. If after being exposed to extreme temperatures and/or extreme relative humidities, the cable ties must be allowed to be stored at room temperature and at least 50% humidity (recommended 80%RH) for at least 24 hrs in a sealed bag before being used again

	NAME	DATE	CAMBRIDGE 960 Alabama Ave, Brooklyn, NY 11207 P:718-649-1666 F:718-485-4403		
DRAWN	J Li	7/30/07			
UNLESS OTHERWISE SPECIFIED:			TITLE: Cambridge Cable Ties 250lb Tensile Strength		
DIMENSIONS ARE IN INCHES [] DENOTES MILLIMETER			SIZE	DWG. NO.	REV
MATERIAL Nylon 6,6 94V-2			A	CT-250 REV A	A
FINISH			DO NOT SCALE DRAWING		
			SCALE: 1:1	WEIGHT:	SHEET 1 OF 1