



Cambridge Part#	Length (L)	Width (W)	Thickness (T)	Max Bundle Dia.
CT6-40	5.91 [150]	0.14 [3.6]	0.04 [1.01]	1.38 [35]
CT8-40	7.87 [200]	0.14 [3.6]	0.04 [1.01]	2.09 [53]
CT11-40	11.81 [300]	0.14 [3.6]	0.04 [1.01]	2.99 [76]

*Please Inquire About Other Sizes Not Listed

**See Cambridge Catalog for Colors and Packaging Options



PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF CODA RESOURCES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF CODA RESOURCES IS PROHIBITED.

Rated Operating Temperatures:
 -40°F to 185°F (-40°C to 85°C)

Usage Recommendations:

The cable ties must be stored at room temperature in at least 50% humidity (recommended 80%RH) in a completely sealed polyethylene bag if not being used. In extreme heat and cold, limit the exposure of unused cable ties. If after being exposed to extreme temperatures and/or extreme relative humidities, the cable ties must be allowed to be stored at room temperature and at least 50% humidity (recommended 80%RH) for at least 24 hrs in a sealed bag before being used again

	NAME	DATE	CAMBRIDGE 960 Alabama Ave, Brooklyn, NY 11207 P:718-649-1666 F:718-485-4403	
DRAWN	J Li	10/17/06		
UNLESS OTHERWISE SPECIFIED:			TITLE:	
DIMENSIONS ARE IN INCHES [] DENOTES MILLIMETER			Cambridge Cable Ties 40lb Tensile Strength	
MATERIAL Nylon 6,6 94V-2			SIZE A	DWG. NO. CT-40 REV A
FINISH				REV A
DO NOT SCALE DRAWING			SCALE: 1:1	WEIGHT:
				SHEET 1 OF 1