



Cambridge Part#	Length (L)	Width (W)	Thickness (T)	Max Bundle Dia.
CT8-50	7.87 [200]	0.19 [4.8]	0.054 [1.37]	1.97 [50]
CT11-50	11.02 [280]	0.19 [4.8]	0.054 [1.37]	2.76 [70]
CT14-50	14.57 [370]	0.19 [4.8]	0.054 [1.37]	4.02 [102]
CT17-50	16.93 [430]	0.19 [4.8]	0.054 [1.37]	4.33 [110]
CT36-50	36.42 [925]	0.19 [4.8]	0.054 [1.37]	10.35 [263]

*Please Inquire About Other Sizes Not Listed
 **See Cambridge Catalog for Colors and Packaging Options



PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF **CODA RESOURCES**. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF **CODA RESOURCES** IS PROHIBITED.

Rated Operating Temperatures:
 -40°F to 185°F (-40°C to 85°C)
 Usage Recommendations:
 The cable ties must be stored at room temperature in at least 50% humidity (recommended 80%RH) in a completely sealed polyethylene bag if not being used. In extreme heat and cold, limit the exposure of unused cable ties. If after being exposed to extreme temperatures and/or extreme relative humidities, the cable ties must be allowed to be stored at room temperature and at least 50% humidity (recommended 80%RH) for at least 24 hrs in a sealed bag before being used again

	NAME	DATE	CAMBRIDGE 960 Alabama Ave, Brooklyn, NY 11207 P:718-649-1666 F:718-485-4403		
DRAWN	J Li	10/17/06			
UNLESS OTHERWISE SPECIFIED:			TITLE: Cambridge Cable Ties 50lb Tensile Strength		
DIMENSIONS ARE IN INCHES [] DENOTES MILLIMETER			SIZE	DWG. NO.	REV
MATERIAL Nylon 6,6 94V-2			A	CT-50 Rev A	A
FINISH			DO NOT SCALE DRAWING	SCALE: 1:1	WEIGHT: SHEET 1 OF 1