



Cambridge Part#	Length (L)	Width (W)	Tensile Strength	Max Bundle Dia.	Hole Dia.	Panel Thickness
CTP5-30	5.12 [130]	0.13 [3.2]	30 lbs	1.1 [28]	0.157 [4.0]	0.079 [2.0]
CTP7-50	7.87 [200]	0.19 [4.8]	50 lbs	1.77 [45]	0.252 [6.4]	0.126 [3.2]

\*Please Inquire About Other Sizes Not Listed

\*\*See Cambridge Catalog for Colors and Packaging Options



**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF CODA RESOURCES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF CODA RESOURCES IS PROHIBITED.

Rated Operating Temperatures:  
 -40°F to 185°F (-40°C to 85°C)

Usage Recommendations:

The cable ties must be stored at room temperature in at least 50% humidity (recommended 80%RH) in a completely sealed polyethylene bag if not being used. In extreme heat and cold, limit the exposure of unused cable ties. If after being exposed to extreme temperatures and/or extreme relative humidities, the cable ties must be allowed to be stored at room temperature and at least 50% humidity (recommended 80%RH) for at least 24 hrs in a sealed bag before being used again

	NAME	DATE	<b>CODA RESOURCES</b> 960 Alabama Ave, Brooklyn, NY 11207 P:718-649-1666 F:718-485-4403		
DRAWN	RH	01-08-10			
UNLESS OTHERWISE SPECIFIED:			TITLE: Cambridge Push Mount Cable Ties		
DIMENSIONS ARE IN INCHES [ ] DENOTES MILLIMETER			SIZE	DWG. NO.	REV
MATERIAL Nylon 6,6 94V-2			<b>A</b>	CTP REV A	<b>A</b>
FINISH			SCALE: 1:1	WEIGHT:	SHEET 1 OF 1
DO NOT SCALE DRAWING					