

Rev.	Date	Notes
A	11/11/09	Initial Release

7/16" Hex Nut
W/ Nylon Insert

SAE SIZE
3MM FONT HEIGHT MIN

CLAMPING RANGE IN AND MM
2.5MM FONT HEIGHT MIN

[0.6]
0.024

Ø DIA

[19]
0.748

PART #	MIN DIA(MM)	MAX DIA(MM)
STB-44P	2-1/4" (57.2)	2-9/16" (65)
STB-72P	3-1/8" (79.5)	3-7/16" (87.4)
STB-88P	3-5/8" (92.2)	3-15/16" (100.1)
STB-116P	4-1/2" (114.3)	4-13/16" (122.2)
STB-148P	5-1/2" (139.7)	5-13/16" (147.6)



PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF **CODA RESOURCES**. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF **CODA RESOURCES** IS PROHIBITED.

Notes:

1. Meets SAE J1508 Specification
2. RoHS Compliant - No Hexavalent Chromium - Cr(VI)
3. Material: Band and Bridge - 301 Series Stainless Steel
All Other Components - Zinc Plated
4. T-Bolt: 1/4"-20 Thread
5. Recommended Installation Torque 75 in*lbs
6. All surface to be clean and polished
7. Parts to be free of burrs and sharp edges

NAME	DATE	CODA RESOURCES 960 Alabama Ave, Brooklyn, NY 11207 P:718-649-1666 F:718-485-4403	
DRAWN	RH		
UNLESS OTHERWISE SPECIFIED:		TITLE:	
DIMENSIONS ARE IN INCHES [] DENOTES MILLIMETER TOLERANCES x.xx ± 0.02 [0.51] x.xxx ± 0.005 [0.13]		HEAVY DUTY T-BOLT CLAMPS	
MATERIAL	SEE NOTES	SIZE	DWG. NO.
FINISH		A	STB-XP
DO NOT SCALE DRAWING		SCALE: 1:1	WEIGHT:
		SHEET 1 OF 1	